



**STANDARD SPECIFICATIONS**

| Model/Size (lbs)          | 6             | 10            | 20            | 30            | 40            |
|---------------------------|---------------|---------------|---------------|---------------|---------------|
| Height (in)               | 22.5          | 15.9          | 20.2          | 25.9          | 32.1          |
| LPG Capacity (gal)        | 1.4           | 2.4           | 4.7           | 7.1           | 9.4           |
| Water Capacity (lbs)      | 15            | 23.8          | 47.6          | 71.5          | 95.2          |
| Nominal Tare Weight (lbs) | 8.1           | 9.7           | 13.0          | 16.5          | 19.5          |
| Cylinder Diameter (in)    | 6.3           | 10.3          | 12.3          | 12.3          | 12.3          |
| Cylinder Volume (cu. in)  | 415           | 664           | 1,318         | 1,999         | 2,635         |
| Collar Diameter (in)      | 5.7           | 7.9           | 7.9           | 7.9           | 7.9           |
| Collar Height (in)        | 6.5           | 5.5           | 5.5           | 5.5           | 5.5           |
| Footring Diameter (in)    | 6.2           | 8             | 8             | 8             | 8             |
| Horizontal Design         | -             | Available     | Available     | Available     | Available     |
| Valve                     | CGA-791 w/OPD | CGA-791 w/OPD | CGA-791 w/OPD | CGA-791 w/OPD | CGA-791 w/OPD |
| Standard Specification    | DOT-4E260     | DOT-4E240     | DOT-4E240     | DOT-4E240     | DOT-4E240     |

**METRIC SPECIFICATIONS**

| Model/Size (lbs)          | 6             | 10            | 20            | 30            | 40            |
|---------------------------|---------------|---------------|---------------|---------------|---------------|
| Height (in)               | 571           | 404           | 513           | 658           | 814           |
| LPG Capacity (gal)        | 5.4           | 9.1           | 17.3          | 26.9          | 35.6          |
| Water Capacity (lbs)      | 6.8           | 10.8          | 21.6          | 32.4          | 43.2          |
| Nominal Tare Weight (lbs) | 3.7           | 4.4           | 5.9           | 7.5           | 8.8           |
| Cylinder Diameter (in)    | 160           | 261           | 312           | 312           | 312           |
| Cylinder Volume (cu. in)  | 6.8           | 10.8          | 21.6          | 32.7          | 43.5          |
| Collar Diameter (in)      | 144.8         | 200           | 200           | 200           | 200           |
| Collar Height (in)        | 165           | 140           | 140           | 140           | 140           |
| Footring Diameter (in)    | 158           | 203           | 203           | 203           | 203           |
| Horizontal Design         | -             | Available     | Available     | Available     | Available     |
| Valve                     | CGA-791 w/OPD | CGA-791 w/OPD | CGA-791 w/OPD | CGA-791 w/OPD | CGA-791 w/OPD |
| Standard Specification    | DOT-4E260     | DOT-4E240     | DOT-4E240     | DOT-4E240     | DOT-4E240     |

All dimensions are approximate