STANDARD SPECIFICATIONS

Model	7.5 INCH	9.5 INCH	12 INCH
Height (in)	14.6	16.4	17.6
Water Capacity (lb)	15.8	29.7	49.6
Diameter (in)	7.5	9.5	12
Cylinder Volume (CU. IN)	438	822	1,378
Standard Specification	**DOT-39**	**DOT-39**	**DOT-39**
Service Pressure (PSIG)	260 | 400	260 | 300 | 400	260 | 320
Test Pressure (PSIG)	325 | 500	325 | 400 | 500	325 | 400

All dimensions are approximate.
Recommended service pressure is dependent on gas type.

FEATURES

Rounded edges for safe handling
Comfort grip for improved handling
Arched design for light weight, enhanced durability and increased strength
Wide 3.2" opening for easy valve access and filling

PRESSURE RELIEF DEVICES

All cylinders are made to DOT-39 specifications.

STAMPS OF AUTHENTICITY

Guranteed Quality. Guranteed Worthington.



CONTAINER COLOR GUIDELINES

Worthington complies with AHRI Guideline N, which states all refrigerant containers will be painted PMS 413. Per SAE, containers with R-134a Automotive will remain PMS 2975. Containers with flammable refrigerant will have a red band on the shoulder.

200 Old Wilson Bridge Road
Columbus, Ohio 43085

P: +1.614.438.3013
Toll-free: 866.928.2657
worthingtonenterprises.com/refrigerant

WORTHINGTON ENTERPRISES

© Worthington Enterprises X/24

METRIC SPECIFICATIONS

Model	7.5 INCH	9.5 INCH	12 INCH
Height (mm)	396.8	416.7	446
Water Capacity (kg)	7.04	13.2	22.1
Diameter (mm)	190.5	241.3	304.8
Cylinder Volume (L)	7.2	13.5	22.5
Standard Specification	**DOT-39**	**DOT-39**	**DOT-39**
Service Pressure (BAR)	17.9 | 27.6	17.9 | 20.7 | 27.6	17.9 | 22.1
Test Pressure (BAR)	23 | 34.5	23 | 27.6 | 34.5	23 | 27.6

All dimensions are approximate.
Recommended service pressure is dependent on gas type.

FEATURES

Rounded edges for safe handling
Comfort grip for improved handling
Arched design for light weight, enhanced durability and increased strength
Wide 3.2" opening for easy valve access and filling

PRESSURE RELIEF DEVICES

All cylinders are made to DOT-39 specifications.

STAMPS OF AUTHENTICITY

Guranteed Quality. Guranteed Worthington.



CONTAINER COLOR GUIDELINES

Worthington complies with AHRI Guideline N, which states all refrigerant containers will be painted PMS 413. Per SAE, containers with R-134a Automotive will remain PMS 2975. Containers with flammable refrigerant will have a red band on the shoulder.

200 Old Wilson Bridge Road
Columbus, Ohio 43085

P: +1.614.438.3013
Toll-free: 866.928.2657
worthingtonenterprises.com/refrigerant

WORTHINGTON ENTERPRISES

© Worthington Enterprises X/24